



BAY RUNNER SPECIFICATIONS

BAY RUNNER INSULATION SYSTEMS™



Machine Specifications

Machine dimensions: 30" X 130"

Machine weight with guardrail: 140 lbs

Guardrail weight: 32 lbs

Max machine weight with maximum roll width and length: 350 lbs +/- 3%

Roll Specifications

Roll fabric dimensions (maximum):
12 ft. width x 500 ft. length

Roll fabric weight at maximum width and length:
208 lbs +/- 5%

Crate Specifications

Crate dimensions: 4' W x 13'8" L x 6'4"H

Crate weight: 1,675 lbs

Crate machine capacity: 6 machines

Crate weight with 6 fully loaded machines:
3,775 lbs +/- 2%



Recommended Sling Specifications

Recommended minimum sling specs to lift one machine:

1" x 10', 1 ply, class 7 polyester sling, with max. 1,600 lbs vertical, 1,280 lbs choker, 3,200 lbs basket

Fall Prevention

OSHA 29 CFR 1926.754(e)(3)(i) - Covers for roof and floor openings shall be capable of supporting, without failure, twice the weight of the employees, equipment and materials that may be imposed on the cover at any one time. ***Bay Runner Insulation Systems supported 1,033 lbs**

Fall Protection

OSHA 29 CFR 1926.502(b)(3) - Guardrail systems shall be capable of withstanding, without failure, a force of at least 200 lbs (890 N) applied within 2 inches (5.1 cm) of the top edge, in any outward or downward direction, at any point along the top edge. ***Bay Runner Insulation Systems guardrail withstood 214 lbs**

OSHA 29 CFR 1926.502(b)(4) - When the 200 lb (890 N) test load specified in paragraph (b)(3) of this section is applied in a downward direction, the top edge of the guardrail shall not deflect to a height less than 39 inches (1.0 m) above the walking/working level. ***Bay Runner Insulation Systems guardrail withstood 344 lbs**

*Intertek Test Report No. 104050471CRT-002, dated December 3, 2019



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications. EFFECTIVE: 11/20

www.BayInsulation.com